CLOCK RECOVERY CIRCUIT

BACKGROUND OF THE INVENTION

The present invention relates to a clock recovery

5   circuit for recovering, from an input signal digitalized, a

clock which synchronizes with the input signal.

In a data reproducing apparatus for data reproduction by

decoding a data signal recorded on a recording medium such

as an optical disk and a magnetic disk, a reproduction

10 signal from the recording medium is identified as data,

therefore necessitating recovery of a clock in

synchronization with the reproduction signal from the

reproduction signal.

For example, data, 8/16 modulated according to an RLL (2,

15 10) modulation code, are stored in a DVD disk. If the

recording channel bit is T, then the pulse width of a

reproduction data series falls in the 3T-11T range. Actual

reproduction data is in the form of an analog waveform as

shown in Figure **8** owing to the MTF characteristic of an

20 optical head. This analog waveform is subjected to

sampling by an A/D converter for digitalization. Clock

recovery from the reproduction signal thus digitalized is

carried out.

As a method for recovery of a clock in synchronization

25 with a reproduction signal when the output of an A/D

converter is represented by the 2's complement, there is

1

given a technique using the zero-crossing point of reproduction data. In such a technique, a phase error proportional to the sample value of the reproduction signal identified as a zero-crossing point is calculated and a PLL

5   (phase locked loop) for clock recovery operates so that the phase error becomes zero.

Apart from the above, if characteristic degradation or defocus occurs in the optical head, this may result in reproduction signal degradation and misidentification of a

10   zero-crossing point. For the case of DVD disks, such a misidentification is likely to take place at 3T in which the reproduction signal has its shortest pulse width (high frequency).

Referring to Figure **9**, there is illustrated an example

15   of a degraded reproduction signal in the optical disk apparatus. According to the example of Figure **9**, in spite of the fact that it is a sample value Zt (cycle 79) that must be distinguished as an actual zero-crossing point when the variation pattern of a reproduction signal is a 3T

20   pattern, the cross detection part of the conventional clock recovery circuit will misidentify a sample value Z (cycle 80) next to the sample value Zt as a zero-crossing point. When the zero-crossing point of a reproduction signal is misidentified in the way as described above, the direction

25   of phase error is taken in a wrong direction. As a result,

the lock of the PLL for clock recovery is unlocked.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide protection against unlocking of the PLL by preventing a phase error misdetected in the clock recovery circuit from being utilized.

In order to achieve the above object, a clock recovery circuit according to the present invention employs an arrangement in which, when it becomes clear that a variation pattern of the input signal indicates a specified pattern (for example, a 3T pattern for DVD disks), for example, the reliability of detecting a zero-crossing point is considered low and no phase error estimated will be utilized for PLL control.

More specifically, the present invention provides a clock recovery circuit comprising a clock generation part for generating a clock signal, a phase error detection part for detecting the phase error of the input signal with respect to the clock signal, and a control part for controlling, based on an output of the phase error detection part, an oscillation frequency of the clock generation part so that the phase error becomes zero, wherein the phase error detection part includes a cross detection part for generating a timing signal representative of a point at which the input signal crosses

3

a preset value, a phase error estimation part for estimating, based on the timing signal, the phase error of the input signal with respect to the clock signal, a pattern detection part for detecting the variation pattern of the input signal, and a selection part for selecting, according to the detected variation pattern, whether the estimated phase error is output to the control part.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram showing an example of an arrangement of a reproduction system signal processing circuit in an optical disk apparatus making utilization of a clock recovery circuit according to the present invention.

Figure 2 is a block diagram showing an example of an arrangement of the clock recovery circuit in Figure 1.

Figure 3 is a circuit diagram showing an example of an arrangement of the pattern detection part in Figure 2.

Figure 4 is a conceptual diagram for providing the description of a principle of the operation of the pattern detection part in Figure 2.

Figure 5 is a circuit diagram showing an example of an arrangement of a pattern detection part to which the principle of Figure 4 is applied.

Figure 6 is a conceptual diagram for providing the description of another principle of the operation of the pattern detection part in Figure 2.

Figure **7** is a circuit diagram showing an example of an arrangement of a pattern detection part to which the principle of Figure **6** is applied

Figure **8** is a waveform diagram showing examples of recorded data and a reproduction signal in an optical disk.

Figure **9** is a waveform diagram showing an example of a reproduction signal degraded.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, examples of applications of the present invention to a clock recovery circuit in a DVD disk reproduction system will be described.

Referring to Figure **1**, there is shown an example of a reproduction system signal processing circuit in an optical disk apparatus making utilization of a clock recovery circuit according to the present invention. Shown in Figure **1** are an optical (DVD) disk **10**, an optical head **11**, an AGC circuit **12** for amplification correction of the reproduction signal, an analog filter **13**, an A/D converter **14**, a digital filter **15** for waveform correction, a maximum likelihood decoder **16**, and a clock recovery circuit **17** according to the present invention.

With the arrangement of Figure **1**, the optical disk **10** is illuminated with reproduction light from the optical head **11**. While causing the reproduction light to trace a pit string formed on the surface of the optical disk **10**, the

5

optical head **11** detects a ray of reflected light. Reflected light is shifted in its phase depending on the presence or absence of pits. Accordingly, the optical head **11** obtains light, whose brightness changes depending on the presence or absence of pits, by superimposition of the reflected light and the reproduction light, wherein the light thus obtained is converted by a photodetector into an electric signal. A reproduction signal obtained by the optical head **11** is amplified by the AGC circuit **12** and then waveform equalized by the analog filter **13**. The output of the analog filter **13** is fed to the A/D converter **14**. The A/D converter **14** digitalizes an analog signal supplied. The reproduction signal thus digitalized is subjected to waveform correction in the digital filter **15** so that it exhibits a desired reproduction characteristic and thereafter converted into decoded data by the maximum likelihood decoder **16**. Further, the reproduction signal digitalized in the A/D converter **14** is input also to the clock recovery circuit **17**. The clock recovery circuit **17** recovers, from the input signal, a clock which synchronizes with the input signal. An output clock (a recovery clock) from the clock recovery circuit **17** serves as a sampling clock for digitalization in the A/D converter **14** and also as a system clock for digital components such as the digital filter **15** and the maximum likelihood decoder **16**.

6

Referring to Figure **2**, there is shown an example of an arrangement of the clock recovery circuit **17** in Figure **1**. Shown in Figure **2** are a phase error detection part **20**, a control part **30**, and a clock generation part **40**. The clock generation part **40** generates a frequency-variable clock signal so that a recovery clock is supplied. The phase error detection part **20** receives, as its input signal, an output sample value from the A/D converter **14**, i.e., a digitalized reproduction signal (hereinafter, referred to just as the reproduction signal) and detects the phase error of the reproduction signal with respect to the recovery clock. Based on the result of the phase error detection by the phase error detection part **20**, the control part **30** controls the oscillation frequency of the clock generation part **40** so that the phase error becomes zero.

Included in the phase error detection part **20** are a cross detection part **21**, a phase error estimation part **22**, a pattern detection part **23**, and a selection part **24**. The cross detection part **21** detects a point at which the reproduction signal zero-crosses. More specifically, at the time when zero-crossing is detected, a signal of Hi (HIGH) level as a timing signal is output from the cross detection part **21** for only one cycle. The phase error estimation part **22** estimates, from a reproduction signal when a Hi-level timing signal is output from the cross

7

detection part **21**, the phase error of the reproduction signal with respect to the recovery clock. The pattern detection part **23** is a circuit block for detecting the variation pattern of a reproduction signal. Here, the

5 description has been made in terms of a clock recovery circuit in a DVD-disk reproduction system and the pattern detection part **23** in Figure **2** is therefore intended for detection of whether the variation pattern of a reproduction signal is a 3T pattern. Further, suppose that

10 a variation pattern detection signal /3T that is output from the pattern detection part **23** indicates a Lo (LOW) level when a 3T pattern is detected, whereas it indicates a Hi level when other than the 3T pattern is detected. The selection part **24** is a circuit block which selects the

15 result of the phase error estimation if the variation pattern detection signal /3T is at Hi level. On the other hand, zero is selected if the variation pattern detection signal /3T is at Lo level. Then, the selection part **24** outputs a phase error detection signal to the control part

20 **30.**

That is, in the clock recovery circuit **17** of Figure **2**, if it becomes clear that the variation pattern of the reproduction signal indicates a 3T pattern, the reliability of detection of the zero-crossing point is considered low

25 and no phase error estimation value will be utilized for

PLL control. This guarantees that the clock recovery circuit **17** operates stably.

Hereinafter, first to third arrangement examples of the pattern detection part **23** in Figure **2** will be explained one after another.

FIRST ARRANGEMENT EXAMPLE

It is seen from Figure **9** that the number of consecutive positive sample values (cycles 80 and 81) becomes extremely reduced in a 3T pattern in which conventional misidentification of a zero-crossing point occurs. The same is true for the case that the number of consecutive negative sample values becomes extremely reduced.

The first arrangement example of the pattern detection part **23** shown in Figure **3** detects, based on such a principle, the presence or absence of a 3T pattern. Shown in Figure **3** are an MSB hold part **50**, a comparison part **60**, and a logical circuit part **65**. The MSB hold part **50** is made up of nine 1-bit latches **51-59** and holds the respective most significant bits of sample values given (i.e., the sign bits in 2's complement representation) as time series data. The comparison part **60** is made up of four 9-bit comparators **61-64** and compares data items stored in the MSB hold part **50** with preset variation patterns. Here, these four preset patterns are "000011111', "111100000", "000001111" and "111110000". This is based on

the viewpoint that there are either at least four consecutive positive sample values or at least four consecutive negative sample values if the variation pattern of the reproduction signal is other than the 3T pattern.

5 That is, if the variation pattern of the reproduction signal is a 3T pattern, no agreement is established in any one of the four 9-bit comparators **61-64** and all of the outputs of these comparators **61-64** are made LOW. The logical circuit part **65** comprises a 4-input OR gate for

10 generation of the variation pattern detection signal /3T from the outputs of the comparators **61-64**. In other words, the variation pattern detection signal /3T is made LOW if the variation pattern is a 3T pattern.

SECOND ARRANGEMENT EXAMPLE

15 Referring to Figure **4**, there is shown another principle of the operation of the pattern detection part **23** in Figure **2**. That is, according to this principle, if the variation pattern of the reproduction signal is other than the 3T pattern, the absolute values of sample values, one of which

20 is ahead by two sample positions from a sample value Z distinguished as a zero-crossing point and the other of which is behind by two sample positions from the sample value Z, are greater than the absolute values of preset threshold values (TH+ on the + side and TH- on the - side)

25 and have different signs.

10

The second arrangement example of the pattern detection part **23** shown in Figure **5** employs such a principle for detecting the presence or absence of a 3T pattern. Shown in Figure **5** are a sample hold part **70**, a comparison part **80**, and a logical circuit part **90**. The sample hold part **70** is made up of five multibit latches **71-75** and holds sample values given as time series data. The comparison part **80** is made up of four multibit comparators **81**, **82**, **84**, and **85** and two 2-input OR gates **83** an **86**. In the comparators **81** and **82** and the OR gate **83**, the data item stored in the first-stage latch **71** of the sample hold part **70** is compared in size with the threshold value TH+ and with the threshold value TH- and a signal of Hi level is supplied whenever the first-stage latch data is greater in absolute value than the threshold values. In the comparators **84** and **85** and the OR gate **86**, the data item stored in the last-stage latch **75** of the sample hold part **70** is compared in size with the threshold value TH+ and with the threshold value TH- and a signal of Hi level is supplied whenever the last-stage latch data is greater in absolute value than the threshold values. The logical circuit part **90** is made up of an exclusive OR gate **91** and a 3-input AND gate **92** for generation of the variation pattern detection signal /3T. That is, if the outputs of the two 2-input OR gates **83** and **86** in the comparison part **80** are both at Hi level and, in

11

addition, if the data stored in the first- and last-stage latches **71** and **75** in the sample hold part **70** differ in sign from each other, this indicates other than the 3T pattern as shown in Figure **4**, so that the variation pattern detection signal /3T is made HIGH. On the other hand, if the variation pattern is a 3T pattern, then the variation pattern detection signal /3T is made LOW.

Further, as the threshold values TH+ and TH- in such a case, the threshold values of a Viterbi decoder in a reproduction system of a conventional optical disk can be used. Of the data items stored in the sample hold part **70**, three or more data items may be compared in size with preset threshold values.

THIRD ARRANGEMENT EXAMPLE

Referring to Figure **6**, there is shown still another principle of the operation of the pattern detection part **23** in Figure **2**. That is, according to this operation, if the variation pattern is other than the 3T pattern, the differential value of two preceding samples and the differential value of two following samples with respect to the sample value Z distinguished as a zero-crossing point have the same sign.

The third arrangement example of the pattern detection part **23** shown in Figure **7** employs this principle and detects the presence or absence of a 3T pattern. Shown in

Figure **7** are a sample hold part **100**, a subtraction part **110**, an MSB hold part **120**, and a logical circuit part **130**. The sample hold part **100** is made up of two multibit latches **101** and **102** and holds sample values given as time series data. 5 The subtraction part **110** sequentially calculates the differential of two consecutive data items stored in the sample hold part **100**. The MSB hold part **120** is made up of three 1-bit latches **121-123** and holds the respective most significant bits (the sign bits) of the serial output of 10 the subtraction part **110** as time series data. The logical circuit part **130** comprises an exclusive NOR gate so that the variation pattern detection signal /3T is formed of the I/O data items of the MSB hold part **120**. That is, if the output of the subtraction part **110** and the output of the 15 last-stage latch **123** of the MSB hold part have the same sign, this indicates other than the 3T pattern as shown in Figure **6**. Accordingly, the variation pattern detection signal /3T is made HIGH. On the other hand, if the variation pattern is a 3T pattern, then the variation 20 pattern detection signal /3T is made LOW.

The examples of the applications of the present invention to a clock recovery circuit in the reproduction system of the DVD disk have been explained. However, the present invention is not limited to these applications. 25 Further, if the input signal of the clock recovery circuit

13

is a digital signal represented by other than the 2's complement representation, a phase error is detected based on a point at which the input signal crosses a preset value other than zero.

5